

## GZG系列振动给料机

### GZG Series Vibrating Feeder



#### GZG系列振动给料机适用范围

振动给料机在生产流程中，可把块状、颗粒状物料从贮料仓中均匀、定时、连续地给到受料装置中去，在砂石生产线中，可为破碎机械连续均匀地喂料，并对物料进行粗筛分，广泛用于冶金、煤矿、选矿、建材、化工、磨料等行业的破碎、筛分联合设备中。

GZG Series Vibrating Feeder is widely used in mine metallurgy, coal, building material, machinery and other industries. It functions feeding the massive, granular and powdery materials from silos or funnels in a row, or even quantitatively to the receptacle equipments, e.g. Feeding to the conveyor, bucket elevator and screens; or to the crushing, grinding machines and so on.

#### 技术参数 Technical Data:

型号 Model	最大进料粒度 Max Feeding Size (mm)	振动频率 Vibrating Speed (r/min)	双振幅 Double Amplitude (mm)	处理能力 Capacity (t/h)		电机功率 Motor Power (kw)	筛面尺寸 Size of Funnel (mm)	外形尺寸 Overall Dimension (mm)	重量 Weight (kg)
				直线筛 Horizontal	-10°				
GZG40-4	100	1450	4	30	40	2×0.25	400×1000×200	1337×750×600	171
GZG50-4	150	1450	4	60	85	2×0.25	500×1000×200	1374×800×630	202
GZG63-4	200	1450	4	110	150	2×0.50	630×1250×250	1648×1000×767	379
GZG70-4	200	1450	4	120	170	2×0.50	700×1290×250	1548×1010×787	389
GZG80-4	250	1450	4	160	230	2×0.75	800×1500×250	1910×1188×850	563
GZG90-4	250	1450	4	180	250	2×0.75	900×1483×250	2003×1178×960	613

GZG100-4	300	1450	4	270	380	2×1.1	1000×1750×250	2190×1362×900	762
GZG110-4	300	1450	4	300	420	2×1.1	1100×1673×250	2151×1362×970	854
GZG125-4	350	1450	4	460	650	2×1.5	1250×2000×315	2540×1500×1030	1099
GZG130-4	350	1450	4	480	670	2×1.5	1300×2040×300	2544×1556×1084	1117
GZG150-4	500	1450	3.5	720	1000	2×2.25	1500×2250×300	2794×1776×1220	1477
GZG160-4	500	1450	4	770	1100	2×2.25	1600×2500×315	3050×1850×1110	1555
GZG180-4	500	1450	3	900	1200	2×2.25	1800×2325×375	2885×2210×1260	2350
GZG200-4	500	1450	2.5	1000	1400	2×2.25	2000×3000×400	3490×2400×1220	2705
GZG150-6	500	960	5	780	1080	2×3	1500×1800×400	2500×1864×1412	1441